



PERFECTION

Advanced Floor Coating

DESCRIPTION

PERFECTION is a cutting edge, technologically advanced pure virgin polymer system combined with a proprietary blend of synthetic waxes produces the most versatile floor coating. This unique product exhibits excellent leveling, fast drying and curing. The extra hard film formation gives this product wearability advantages and the versatility to maintain the coating with low speed, conventional, high speed and ultra-high speed maintenance procedures. Recommended for all floors that will tolerate a water-based floor sealer/ finish.

PRODUCT FEATURES / BENEFITS

- Sealer/Finish combination / Simplifies floor care system
- May be used with conventional, high speed or ultra-high speed maintenance systems / Allows versatility and reduced inventory levels of additional products
- Very scratch and scuff resistant / Extra hard wear surface
- High solids formulation / Offers labor and material savings
- Pure acrylic polymers / Responsive to high speed and ultra high speed burnishing

DIRECTIONS FOR USE

Can be used on any hard surface that will tolerate water-based coatings. Gives outstanding performance on vinyl, vinyl composition, asphalt, rubber, worn no-wax, asbestos and linoleum resilient flooring. Can also be used for concrete, terrazzo, quarry tile, sealed wood and cork.

Floor Preparation: Strip old finish and wax using your preferred NCL floor stripper following label directions. For baseboards and corners, use an NCL baseboard stripper following label directions. If necessary, rinse thoroughly with clean water and allow to completely dry.

Application: Using a clean mop or applicator apply a thin uniform coats of PERFECTION™ Advanced Floor Coating. Allow to dry for a minimum of 30 minutes after each coat. Do not apply more

than 4 coats in a 24 hour period. Floor should be thoroughly dry before traffic is allowed in area.

High Speed Buffing and Burnishing: PERFECTION™ Advanced Floor Coating is an ideal product for use with high speed polishing or burnishing machines of 1000 rpm or higher. Prior to high speed buffing or burnishing dust mop the floor surface using an NCL dust mop treatment. Buff or dry burnish using an approved buffing pad. For spray buffing, mop-on or autoscrubber restoring use a preferred NCL gloss restorer.

Routine Maintenance: Dust mop using mop treated with an NCL dust mop treatment. Damp mop or clean with an automatic scrubber using your preferred NCL neutral floor cleaner following label directions.

SPECIFICATIONS

Type	Pure acrylic polymer	Freeze Thaw Stable	Yes (3 Freeze Thaw Cycles)
pH	8.2 ± 0.3	Detergent Resistant	Yes
Drying Time (minutes)	20-30	Leveling	Excellent
Color	White, opaque liquid	Black Mark Resistance	Superior
Odor	Typical acrylic	Scuff Resistance	Superior
Powdering	None	Soil Resistance	Superior
Film Appearance	Clear	Durability	Excellent
Non-Yellowing	Yes	Recoatibility	Excellent
Flash Point	None	Removability	Excellent
Slip Resistant	Yes	Shelf Life	1 year minimum in original unopened container

SAFETY INFORMATION

KEEP OUT OF THE REACH OF CHILDREN.

Precautionary statement

Prevention: Observe good industrial hygiene practices.

Response: Wash thoroughly after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

KEEP FROM FREEZING

For Commercial and Industrial Use Only



FLOOR CARE



CLASSIFIED
Floor Coating and Finishing Material
As to Slip Resistance Only
18EL



401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com