



SPIT SHINE

Ultra High Speed Kleen & Burnish

DESCRIPTION

A unique burnishing solution designed to clean, repair, protect and enhance floor finish gloss. This blend of penetrants, moisturizers, polishing agents and polymers provides maximum flexibility to floor finishes. Can be applied to floor coating through the use of an auto scrubber or by simply mopping onto the floor. Will produce exceptional results on any type of floor finish.

PRODUCT FEATURES / BENEFITS

- Enhances deep wet look gloss of finish / Maximum user appeal
- Cleans and polishes in one step / Saves labor costs
- Adds protection to wear layer of finish / Increases scuff and scratch resistance
- "Hardens" finish film / Enhanced wearability of floor finish
- Multipurpose formulation / Reduces inventory

DIRECTIONS FOR USE

A premium quality, thermal reactive solution that can be applied to any type of water-based floor finish or sealer. May be used with an auto scrubber or by mopping solution onto the floor. Appropriate for any resilient or stone floor coated with a quality floor finish.

Auto-Scrub Method:

- Dust mop or sweep floor.
- Dilute SPIT SHINE 2-4 ounces per gallon of cool water. Scrub floor with SPIT SHINE and pick up solution.
- Allow floor to dry completely.
- Burnish floor using recommended pad.

Mop-On Method:

- Dust mop or sweep floor.
- Dilute SPIT SHINE 1-2 ounces per gallon of cool water. Mop floor clean with SPIT SHINE and pick up soil with tightly wrung out cleaning mop.
- Allow floor to dry completely.
- Burnish floor using recommended pad.

Spray Buffing:

- Place SPIT SHINE into a trigger sprayer or other suitable spraying device.
- Apply a very light mist of SPIT SHINE to a small area directly in the path of the floor machine and immediately burnish to a high gloss.
- A heavier application may be made directly on black heel marks or heavily worn areas.

SPECIFICATIONS

Type.....	Blended emulsion	Freeze Thaw Stable	Yes (3 cycles)
pH.....	8.8 ± 0.2	Gloss Restoration.....	Outstanding
Color.....	Light blue, opaque liquid	Leveling.....	Excellent
Odor	Puri	Black Mark Resistance.....	Excellent
Film Appearance	Clear	Soil Resistance.....	Superior
Powdering	None	Scuff Resistance.....	Superior
Flash Point	None	Recoatibility.....	Excellent
Slip Resistant	Yes	Durability.....	Excellent
		Shelf Life.....	1 year minimum in original unopened container

SAFETY INFORMATION

KEEP OUT OF THE REACH OF CHILDREN.

Precautionary statement

Prevention: Observe good industrial hygiene practices.

Response: Wash thoroughly after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.


This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

KEEP FROM FREEZING.

For Commercial and Industrial Use Only



RESTORER



CLASSIFIED Floor Coating and Finishing Material
As to Slip Resistance Only
18EL



401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com