



ASAP™

Fast Acting Stripper

DESCRIPTION

An economical fast acting power stripper designed to provide intense, rapid action stripping on even heavily burnished floor finishes, reducing labor cost and overall floor stripping cost expenditures. Ideal for schools, retail floors, office buildings and many other stripping applications.

PRODUCT BENEFITS

- Fast acting, rapid liquefaction of floor finish
- Thoroughly emulsifies even multiple layers of burnished floor finish easily
- Controlled foaming, saves time and labor
- Concentrated, powerful stripper saves product cost by using higher dilution ratios

DIRECTIONS FOR USE

Mop/Wet Vacuum Stripping System:

Follow the dilution chart below (in cold or mildly warm water):

Light/Medium Duty Build-Up:

..... Dilute 1 part ASAP™ to 8 parts water.

Heavy Duty Build-Up:

..... Dilute 1 part ASAP™ to 4 parts water.

Apply liberally with a mop to an area small enough so as not to allow the product to dry and allow to stand for 3 to 5 minutes. Agitate with a mop and remove solution and old finish with a wet vacuum. Allow floor to dry thoroughly and apply new finish as directed by manufacturer. If complete stripping is not accomplished repeat the above procedure before re-application of recommended NCL Floor Finish.

Floor Machine Stripping System: Follow the dilution chart below (in cold or mildly warm water):

Light/Medium Duty Build-Up:

..... Dilute 1 part ASAP™ to 16 parts water.

Heavy Duty Build-Up:

..... Dilute 1 part ASAP™ to 6 parts water.

Allow to stand for 3 to 5 minutes, scrub with a rotary floor machine or automatic scrubber equipped with stripping pads. Remove solution and old finish with a wet vacuum and allow floor to dry completely. If desired, a rinsing step can be added. Apply recommended NCL Floor Finish as per instructions.

Note: Asphalt tile, Linoleum, and other sensitive floor surfaces may be damaged by contact with stripping solution. We recommend that a spot test be conducted before general use.

SPECIFICATIONS

Appearance Clear, Thin Liquid
 Odor Mild characteristic
 pH 13.6 ± 0.4
 Evaporation Rate = To Water
 Solubility In Water Complete
 Specific Gravity (g/cc)..... 1.01 ± 0.01

Upper Cloud > 140°F
 Lower Cloud < 34°F
 Freeze Thaw Stable
 Hard Water Performance Excellent
 Shelf Life 1 year minimum in original unopened container

SAFETY INFORMATION

DANGER: HARMFUL IF SWALLOWED. CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. HARMFUL IF INHALED. MAY CAUSE RESPIRATORY IRRITATION. KEEP OUT OF THE REACH OF CHILDREN.



Precautionary statement

Prevention: Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response: If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents/container in accordance with local authority requirements.


This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

For Commercial and Industrial Use Only



Stripper



401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com