



INVINCIBLE™

Mega-Wear, Low Odor Floor Finish

DESCRIPTION

INVINCIBLE™ is a new floor finish based on NCL's exclusive, proven Micro Molecular Technology. INVINCIBLE™ provides superior "off-the-mop" initial gloss, exceptional film clarity, and "mega-wear". INVINCIBLE™ is exceptionally easy to apply, levels beautifully, and dries quickly. INVINCIBLE™ is uniquely formulated for ideal drying in high humidity conditions. INVINCIBLE™ repels soil, scuffs and scratches to provide long lasting protection and beauty ("mega-wear").

PRODUCT FEATURES / BENEFITS

- Applies easily / Dries quickly, levels beautifully, no re-coat attack.
- High Solids formula / Save time and labor with fewer coats
- Scuff, scratch and abrasion resistant / Minimizes maintenance requirements
- Repels Dirt / Stays clean, clear and bright longer
- Superior "Off-The-Mop" Gloss / Floors look beautiful, right from the start.
- Excellent Burnish Response / Easily maintain wet-look gloss for extended period of time.
- Exclusive Micro Molecular Technology/ Superior durability and long term performance.
- Formulated for high humidity conditions / Dries great in virtually all humidity conditions.

DIRECTIONS FOR USE

FLOOR PREPARATION: Strip old finish or wax using your choice of quality NCL Strippers following label directions. For baseboards, corners, steps or hard to reach areas use **PIZZAZZ™ Baseboard Stripper** following label directions. If necessary, rinse the floor thoroughly with clean water. Allow to completely dry.

APPLICATION: Using a clean finish mop or applicator apply thin uniform coats of **INVINCIBLE™ Mega-Wear / Low Odor Floor Finish**. Allow to dry thoroughly after each coat, usually 20-30 minutes (depends on temperature, humidity, and amount of finish applied). Do not apply more than 4 coats in a 24 hour period. Floor should be thoroughly dry before allowing traffic in area.

BUFFING AND BURNISHING: **INVINCIBLE™ Mega-Wear / Low Odor Floor Finish** is an ideal for use in no-buff or buffing

programs using all speeds of buffing or burnishing machines. Prior to buffing or burnishing make sure the floor is clean, free of dirt and debris. Buff or dry burnish using an approved burnishing pad. For spray buffing, mop-on or autoscrubber restoring use **POP & SHINE™ Gloss Restorer**.

ROUTINE MAINTENANCE: Dust mop using mop treated with **CONTROL™ Dust Mop Treatment**. Damp mop or clean with an automatic scrubber using **ENHANCE™ Neutral Floor Cleaner** following label directions.

SCRUB AND RE-COAT: When routine maintenance and buffing/ burnishing no longer provides the desired response, scrub using **QWIK-SCRUB™ Scrub and Re-coat Cleaner** following label directions and apply 2-3 coats of **INVINCIBLE™ Floor Finish** following directions under APPLICATION.

SPECIFICATIONS

Type	Pure acrylic polymers
Coverage (sq. ft./gal).....	2500 - 3000
pH.....	8.2 ± 0.3
Drying Time (minutes).....	20-30
% Styrene (Free Monomer)	0.0
Specific Gravity (g/cc)	1.03 ± 0.01

Color	White, opaque liquid
Odor.....	Typical acrylic
Powdering.....	None
Flash Point.....	None
Slip Resistant.....	Yes
Shelf Life	1 year minimum in original unopened container

SAFETY INFORMATION

KEEP OUT OF THE REACH OF CHILDREN.

Precautionary statement

Prevention: Observe good industrial hygiene practices.

Response: Wash thoroughly after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of contents/container in accordance with local/ regional/national/international regulations.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

KEEP FROM FREEZING

For Commercial and Industrial Use Only



FLOOR CARE



Floor Coating and Finishing
Material As to Slip
Resistance Only 18EL



401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com



TDS-0595-0523