



PICTURE PERFECT®

*Low Maintenance
High Traffic Floor Finish*

DESCRIPTION

PICTURE PERFECT is a dazzling achievement in floor care technology. This premier high solids floor finish offers the highest initial application gloss and exceptional wear, especially in high traffic areas such as supermarkets, retail stores and large office building lobbies. With Ultra High Speed burnishing, PICTURE PERFECT produces a deep wet look gloss, and requires a minimum of restorative maintenance to save time, labor and money!

PRODUCT FEATURES / BENEFITS

- Combination Sealer/Finish saves product cost
- Maximum scuff and scratch resistance
- Minimum burnishing required to retain showcase appearance
- Designed for high traffic areas

DIRECTIONS FOR USE

Floor Preparation: Strip old finish and wax using your preferred NCL floor stripper following label directions. For baseboards and corners, use an NCL baseboard stripper following label directions. If necessary, rinse thoroughly with clean water and allow to completely dry.

Application: Using a clean mop or applicator apply a thin uniform coat of PICTURE PERFECT® Low Maintenance / Traffic Floor Finish. Allow to dry for a minimum of 30 minutes after each coat. Do not apply more than 4 coats in a 24 hour period. Floor should be thoroughly dry before traffic is allowed in area.

High Speed Buffing and Burnishing: PICTURE PERFECT® Low Maintenance / High Traffic Floor Finish is an ideal product

for use with high speed polishing or burnishing machines of 1000 rpm or higher. Prior to buffing or burnishing dust mop the floor surface using an NCL dust mop treatment. Buff or dry burnish using an approved buffing pad. For spray buffing, mop-on or autoscrubber restoring use a preferred NCL gloss restorer.

Routine Maintenance: Dust mop using mop treated with an NCL dust mop treatment. Damp mop or clean with an automatic scrubber using your preferred NCL neutral floor cleaner following label directions.

Scrub and Recoat: When routine maintenance and buffing/burnishing no longer responds as needed, scrub and recoat using an NCL scrub and recoat cleaner following label directions.

SPECIFICATIONS

Type	Integrated Fusion Polymer	Freeze Thaw Stable	Yes (3 cycles)
Coverage (sq. ft./gal).....	2500 - 3000	Detergent Resistant	Yes
Color	White, Opaque liquid	Leveling	Excellent
Odor	Typical acrylic	Black Mark Resistant	Excellent
pH	8.2 ± 0.3	Scuff Resistant	Excellent
Drying Time (minutes)	30	Resistant of Soiling	Excellent
Specific Gravity (g/cc)	1.03 ± 0.01	Gloss Retention	Excellent
Density (lbs/gal)	8.6 ± 0.1	Immediate Wet Look Gloss	Outstanding
Slip Resistant	Yes	Shelf Life	1 year minimum in original unopened container

SAFETY INFORMATION

KEEP OUT OF THE REACH OF CHILDREN.

Precautionary statement

Prevention: Observe good industrial hygiene practices.

Response: Wash thoroughly after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

KEEP FROM FREEZING

For Commercial and Industrial Use Only



FLOOR CARE



Floor Coating and Finishing Material
As to Slip Resistance Only
18EL



World Class Cleaning & Hygiene Solutions™

401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com



TDS-0580-0623